

Declaration of performance

N° NLD0001-0008-00 (en)

1. Unique identification code of the product-type:

METAL BUILDING PANEL	MW-EN13162-T3-WS
SYSTEMROLL 400	MW-EN13162-T3
FLEX 400	MW-EN-13162-T2-AFr5
CLICKPAN	MW-EN13162-T3-WS

2. Element allowing identification of the construction product:

Unique product name & code as stated under point 1.
See also product label for traceability.

3. Intended use (according harmonised technical specification)

Thermal insulation of Buildings (THiB)

4. Name, registered trade name and contact address of the manufacturer:

SAINT-GOBAIN Construction Products NLD b.v.
Parallelweg 20, 4878 AH, Etten – Leur, Nederland

5. Name and contact address of the authorised representative:

Not applicable

6. System(s) of Assessment and Verification of Constancy of Performance of the construction product:

AVCP System 1 for Reaction to fire (A1, A2, B, C) & AVCP System 3 for other characteristics

7. Case a construction product covered by a harmonised standard:

KIWA (Notified Body n° 0620)

- performed the determination of the product-type on the basis of type testing (including sampling);
initial inspection of the manufacturing plant and of factory production control; continuous
surveillance, assessment and evaluation of factory production control ; under system 1.

BDA (Notified Body n°1640) & KIWA (Notified Body n° 0620)

performed the determination of the product-type on the basis of type testing (based on sampling
carried out by the manufacturer), under system 3.

8. Case of a construction product for which a European Technical Assessment has been issued:

Not applicable

9. Declared performance:

All characteristics listed in the table hereunder are determined in harmonised standard
EN 13162:2012+A1:2015

Essential characteristics Requirement clauses in the European standard	METAL BUILDING PANEL	SYSTEMROLL 400 (diktes < 150 mm)
Thermal resistance and thermal conductivity (4.2.1)	0,038 mW/m.K	
Thickness (4.2.3)	T3	T3
Reaction to Fire (4.2.6)	A1	A1
Water absorption (4.3.7.1)	< 1 kg / m ²	NPD
Water absorption (4.3.7.2)	NPD	NPD
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Air Flow resistivity (4.3.12)	NPD	NPD
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T3-WS	MW-EN13162-T3
CE certificatenummer	41531	41520

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

Essential characteristics Requirement clauses in the european standard	FLEX 400	CLICK-PAN
Thermal resistance and thermal conductivity (4.2.1)	0,038 mW/m.K	
Thickness (4.2.3)	T2	T3
Reaction to Fire (4.2.6)	A1	A1
Water absorption (4.3.7.1)	NPD	< 1 kg / m ²
Water absorption (4.3.7.2)	NPD	NPD
Water vapour transmission (4.3.8)	NPD	NPD
Release of dangerous substances (4.3.13)	NPD	NPD
Sound absorption (4.3.11)	NPD	NPD
Dynamic stiffness (4.3.9)	NPD	NPD
Thickness (4.3.10.2)	NPD	NPD
Compressability (4.3.10.4)	NPD	NPD
Air Flow resistivity (4.3.12)	5 kPa.s/m ²	NPD
Air Flow resistivity (4.3.12)	5 kPa.s/m ²	NPD
Continuous glowing combustion (4.3.15)	NPD	NPD
Compressive stress or compressive strength (4.3.3)	NPD	NPD
Point load (4.3.5)	NPD	NPD
Durability characteristics (4.2.7) ^{a,b}	NPD	NPD
Thermal resistance and thermal conductivity (4.2.1) ^c	NPD	NPD
Durability characteristics (4.2.7) ^d	NPD	NPD
Tensile strength perpendicular to faces ^e (4.3.4)	NPD	NPD
Compressive creep (4.3.6)	NPD	NPD
CE Designation code	MW-EN13162-T2-AFr5	MW-EN13162-T3-WS
CE certificatenummer	41520	41531

^a No change in reaction to fire properties for mineral wool products.

^b The fire performance of mineral wool does not deteriorate with time. The euroclass classification of the product is related to the organic content, which cannot increase in time

^c Thermal conductivity of mineral wool products does not change with time, experience has shown the fibre structure to be stable and the porosity contains no other gasses than atmospheric air

^d For dimensional stability thickness only

^e This characteristic also covers handling and installation

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Mark Rippens
Plantmanager Saint-Gobain Isover



Date: 3-5-2018

Etten – Leur